



BETAETIGER AZ 17/170-B5

- Particularly suitable for sliding doors
- Particularly suitable for sliding doors

Data

Ordering data

Product type description	BETAETIGER AZ 17/170-B5
Article number (order number)	101122895
EAN (European Article Number)	4030661104409
eCl@ss number, Version 9.0	27-27-26-06
eCl@ss number, Version 11.0	27-27-26-06
ETIM number, version 7.0	EC001487
ETIM number, version 6.0	EC001487

General data

Material of the actuator	Stainless steel (V2A)
Gross weight	20 g

Mechanical data

Actuating radius, minimum	140 mm
Actuator	angled

Scope of delivery

Tamperproof screws

Note (General)


minimum actuating radius on rotating guard systems via the narrow edge of the actuator 140 mm

minimum actuating radius on hinged guards in line with the plane of the actuator 200 mm

The axis of the hinge must be 13 mm above and in a parallel plane to the top surface of the safety switch.

Operating instructions and Declaration of conformity

AZ 17/AZM 170 Actuator (117.8 kB, 10.05.2019, Revision D)

Product picture (catalogue individual photo)

| 4.1 MB | .tif | 109 x 130.2 mm - 1090 x 1302 px - 254 dpi
| 308.8 kB | .jpg | 352.778 x 458.258 mm - 1000 x 1299 px -
72 dpi
| 30.3 kB | .png | 73.731 x 95.956 mm - 209 x 272 px - 72 dpi

Technical drawing of a mechanical part. The main view shows a cross-section with dimensions: 12, 30, 22, 15, 36, 2, 23, 6.3, and 4.3. A detail view on the right shows a fillet with a radius of $R \min 200$ and a section line.

| 36.2 kB | .cdr |
| 3.7 kB | .png | 74.083 x 51.506 mm - 210 x 146 px - 72 dpi
| 74.6 kB | .jpg | 352.778 x 245.886 mm - 1000 x 697 px - 72
dpi

Generated on: 11/01/2022, 5:36 am